

16. (New) A facsimile device shown in claim 15, further comprising:
a judging unit for judging whether the transmission of an image data using said computer network is completed or not; and,
a retransmitting unit for transmitting an image data to said communication device in case of judging that said transmission is not completed

17. (New) The facsimile device comprising;
a connecting unit for connecting respectively with the public switched telephone network and the computer communication network; and,
a transmitting unit for transmitting an image data to destination using the network shown in a network information in case of inputting the discrimination information to the destination of the image data, to which the network information showing which network is used is attached.

18. (New) The facsimile device shown in claim 17, wherein a connecting unit for connecting with said public switched telephone network is composed such as to connect with the public switched telephone network via the private branch exchange connected to the internal network, characterized in that said network information shows which network is used among the internal network, the public switched telephone network or the computer communication network.

19. (New) A method of operating a facsimile device, which has a communication unit for communicating via a public switched telephone network, with a communication device connected to said public switched telephone network, and with a gateway device connecting said public switched telephone network to a computer communication network, comprising:

transmitting an image data to said communication device or
transmitting an image data and a discrimination information to said gateway

device, based on the corresponding network information in case of inputting the destination discrimination information of image data and the network information.

20. (New) A method of operating a facsimile device, which has a connecting unit for connecting respectively with the public switched telephone network and the computer communication network, comprising;
transmitting an image data to a destination using the network shown in a network information in case of inputting the discrimination information to the destination of the image data, to which the network information showing which network is used is attached. --
